

United States Patent [19]

Kelly et al.

[11] Patent Number: 4,548,652

[45] Date of Patent: Oct. 22, 1985

[54] METHOD OF PURGING A PLURAL COMPONENT MIXING AND DISPENSING SYSTEM

[75] Inventors: Lawrence S. Kelly, Bolingbrook;
Marty P. McCormick, Palatine;
William A. Weikel, Hanover Park, all
of Ill.

[73] Assignee: Graco Inc., Minneapolis, Minn.

[21] Appl. No.: 674,942

[22] Filed: Nov. 26, 1984

Related U.S. Application Data

[62] Division of Ser. No. 529,346, Sep. 6, 1983, Pat. No. 4,522,789.

[51] Int. Cl.⁴ B01F 5/05; B08B 9/02

[52] U.S. Cl. 134/22.12; 134/22.11;
134/22.18; 134/34; 422/133; 422/135; 422/234

[58] Field of Search 134/34, 36, 22.11, 22.12,
134/22.14, 22.18, 22.19; 422/132, 133, 135, 234;
239/112, 113, 127, 413, 427; 366/136, 137, 159,
173; 222/109; 261/DIG. 26; 521/917

[56] References Cited

U.S. PATENT DOCUMENTS

1,566,596 12/1925 Hardesty .
1,851,338 3/1932 Wemple .
1,925,056 8/1933 Pepper .
2,123,604 7/1938 Johnson .
2,727,786 12/1955 Bede .
3,023,968 3/1962 Mitchell .
3,164,325 1/1965 Veum .

3,240,432 3/1966 Boettler .
3,246,845 4/1966 Techler .
3,829,016 8/1974 Scharfenberger .
4,037,758 7/1977 Bourque .
4,073,664 2/1978 Zwirlein 134/34
4,106,699 8/1978 Holt .
4,138,161 2/1979 Payre .
4,204,977 5/1980 Zwirlein 134/34

Primary Examiner—Barry S. Richman

Assistant Examiner—W. R. Johnson

Attorney, Agent, or Firm—Paul L. Sjoquist

[57]

ABSTRACT

A system and method of operating for mixing and dispensing two liquid components, characterized in that each component is chemically stable when maintained in isolation and chemically reactive when combined with the other component. The system includes separate liquid storage containers and pumps for delivering each of the liquids through a common mixing manifold, and from there to a dispensing apparatus, the system including a further pump in one of the containers for delivering liquid through a valved, closed loop subsystem back to the container, the closed loop having therein an entry point for connection to the dispensing apparatus, and the system including a further valve for controlling the flow of the other liquid component to the dispensing apparatus, whereby the conduits leading to the dispensing apparatus may be purged of mixed liquid components, diluted, and returned to the one storage container.

3 Claims, 1 Drawing Figure

